

PENDANT LIGHT

1998



Please read instructions before commencing installation and retain for future reference.

Connecting the Terminal Block

Connect main supply (brown - live, blue - neutral, green/yellow - earth) into terminal block making sure all connections are tight.

The state of the length of the

SPECIFICATIONS:

- Fitting: Aluminum+ Glass
- Lamp type: E14 MAX 8W
 - Lamps and gears excluded unless otherwise specified
- **Protection against electric shock:** CLASS I. Requires earth connection.
- **Ingress Protection:** IP20. Protection against entry of solid objects greater than 12mm in diameter.
- Quality/Corrosive rating: QC21: Burning period: 12hrs/24hr cycle. Commercial use, indoor mainly painted or plated metals. Not for use in corrosive environments.

INSTALLATION INSTRUCTIONS:

Electrical products can cause death, injury, or damage to property. Installation of this product must be carried out by a qualified electrician.

- Ensure mains supply is switched off.
- Insert masonry plugs into mounting surface.
- Fit mounting bracket onto mounting surface with self-tapping screws
- Connect main supply wires to terminal block making sure all connections are tight.
- Fit ceiling cup onto mounting bracket with screws.
- Fit lamps firmly into lampholders
- Fit glass shade onto ceiling plate by securely placing it into mounting clips
- Reconnect power.

WARNING:

• This fitting must be earthed.







